

EcoHalogen PARs

PAR20, PAR30, PAR30LN, PAR38

(Two Packs)



- Compliant with EISA General Service Incandescent Reflector Standards
- Consumes less energy while delivering equal light output to traditional Halogen PARs
- Ideal for residential and commercial use in recessed lighting, museums, galleries, retail displays, and landscape
- 2 Packs

ECOHALOGEN = HALOGEN

39W = 50W

60W = 75W

70W = 90W

Visit www.bulbrite.com/EISA for additional information



145 WEST COMMERCIAL AVENUE, MOONACHIE, NJ 07074
SHOWROOM & EDUCATION CENTER, DALLAS TRADE MART 3351
T: 800-528-5555 • F: 800-441-7708 • INFO@BULBRITE.COM



BULBRITE
www.bulbrite.com

EcoHalogen PARs

PAR20, PAR30, PAR30LN, PAR38 (Two Packs)

- Compliant with EISA General Service Incandescent Reflector Standards
- Consumes less energy while delivering equal light output to traditional Halogen PARs
- Ideal for residential and commercial use in recessed lighting, museums, galleries, retail displays, and landscape
- 2 Packs

Visit www.bulbrite.com/EISA for additional information

Due to the new energy efficient standards, some of the bulbs you currently use in your home will no longer be available.

Beginning in January 2012, you will have 3 choices of light bulbs: halogen, compact fluorescent (CFL) or light emitting diode (LED).

Of the three, halogen light bulbs are most similar to the incandescent bulbs most people currently use and here's how they measure up.

Benefits	Halogen	CFL	LED
Same Shape	✓		
Similar Brightness	✓	✓	✓
Full Dimmability	✓		
Cost Effective	✓		

ECOHALOGEN = HALOGEN
 39W = 50W
 60W = 75W
 70W = 90W



Pendant / Downlights



Recessed



Track



Landscape



PAR20



PAR30



PAR30LN



PAR38

Watts	Bulb Type	Base	Item #	Ordering Code	Volts	Inner/Master	Beam	Color Temp.	Lumens	M.O.L.	Avg. Rated Life
39	PAR20	E26	682431	H39PAR20SP/ECO/2PK	120	1 (2-PK) / 8 (2-PK)	Spot	2900K	530	3 1/16"	1500
	PAR30	E26	683430	H39PAR30NF/ECO/2PK	120	1 (2-PK) / 8 (2-PK)	N. Flood	2900K	530	3 1/2"	1500
	PAR30LN	E26	683431	H39PAR30NF/L/ECO/2PK	120	1 (2-PK) / 8 (2-PK)	N. Flood	2900K	530	4 3/8"	1500
60	PAR30	E26	683452	H60PAR30SP/ECO/2PK	120	1 (2-PK) / 8 (2-PK)	Spot	3000K	1100	3 1/2"	1500
	PAR30LN	E26	683453	H60PAR30SP/L/ECO/2PK	120	1 (2-PK) / 8 (2-PK)	Spot	3000K	1100	4 3/8"	1500
	PAR38	E26	684450	H60PAR38NF/ECO/2PK	120	1 (2-PK) / 8 (2-PK)	N. Flood	3000K	1100	5 1/8"	1500
70	PAR38	E26	684470	H70PAR38NF/ECO/2PK	120	1 (2-PK) / 8 (2-PK)	N. Flood	3000K	1310	5 1/8"	1500
			684471	H70PAR38SP/ECO/2PK	120	1 (2-PK) / 8 (2-PK)	Spot	3000K	1310	5 1/8"	1500