

SORAA® VIVID AND PREMIUM AR111 DIMMABLE



BULBRITE®

145 West Commercial Ave, Moonachie, NJ 07074
Showroom & Educational Training Center, World Trade Mart #3351
P: 800-528-5555 • F: 800-441-7708 • info@bulbrite.com • www.bulbrite.com



SORAA®

Soraa Inc.
6500 Kaiser Drive
Fremont, CA 94555
510 456 2200

SORAA® VIVID & PREMIUM AR111 DIMMABLE

- Light intensity matches that of standard halogen lamps
- Single light source ensures a single crisp shadow
- Compact, low profile driver electronic uses space economically
- Narrow spot CBCPs of 24,000Cd at 95CRI and 31,000Cd at 80CRI
- Works with trailing edge and leading edge phase cut dimmers
- Automatic safety shut down in any thermal environment not conducive to minimum airflow or proper ventilation
- Ideal for residential and commercial applications most commonly used in recessed and tracking lighting
- VIVID lamps offer excellent color rendering - CRI = 95, R9 = 95
- PREMIUM lamps offer higher light output
- Narrow spot compatible with Soraa SNAP System accessories



DIMMABLE
by design

VIVID
LED = Halogen
18.5W = 75W

PREMIUM
LED = Halogen
18.5W = 100W



	WATTS	BULB TYPE	BASE	ITEM #	ORD. CODE	VOLTS	INNER/MASTER	BEAM ANGLE	COLOR TEMP	CRI	LUMENS	CBCP	AVERAGE RATED LIFE	M.O.L.
VIVID	18.5	AR111	G53	777900	SR111-18-09D-927-03	12	1/20	Spot 9°	2700K	95	930	22400	35,000	2 1/4"
	18.5	AR111	G53	777901	SR111-18-25D-927-03	12	1/20	N. Flood 25°	2700K	95	930	5020	35,000	2 1/4"
	18.5	AR111	G53	777902	SR111-18-36D-927-03	12	1/20	Flood 36°	2700K	95	930	2320	35,000	2 1/4"
	18.5	AR111	G53	777903	SR111-18-60D-927-03	12	1/20	W. Flood 60°	2700K	95	930	1020	35,000	2 1/4"
	18.5	AR111	G53	777904	SR111-18-09D-930-03	12	1/20	Spot 9°	3000K	95	1000	24100	35,000	2 1/4"
	18.5	AR111	G53	777905	SR111-18-25D-930-03	12	1/20	N. Flood 25°	3000K	95	1000	5400	35,000	2 1/4"
	18.5	AR111	G53	777906	SR111-18-36D-930-03	12	1/20	Flood 36°	3000K	95	1000	2500	35,000	2 1/4"
	18.5	AR111	G53	777907	SR111-18-60D-930-03	12	1/20	W. Flood 60°	3000K	95	1000	1100	35,000	2 1/4"
	18.5	AR111	G53	777908	SR111-18-09D-940-03	12	1/20	Spot 9°	4000K	95	1040	25060	35,000	2 1/4"
	18.5	AR111	G53	777909	SR111-18-25D-940-03	12	1/20	N. Flood 25°	4000K	95	1040	5600	35,000	2 1/4"
	18.5	AR111	G53	777910	SR111-18-36D-940-03	12	1/20	Flood 36°	4000K	95	1040	2600	35,000	2 1/4"
	18.5	AR111	G53	777911	SR111-18-60D-940-03	12	1/20	W. Flood 60°	4000K	95	1040	1140	35,000	2 1/4"
	18.5	AR111	G53	777912	SR111-18-09D-950-03	12	1/20	Spot 9°	5000K	95	1050	25300	35,000	2 1/4"
	18.5	AR111	G53	777913	SR111-18-25D-950-03	12	1/20	N. Flood 25°	5000K	95	1050	5660	35,000	2 1/4"
	18.5	AR111	G53	777914	SR111-18-36D-950-03	12	1/20	Flood 36°	5000K	95	1050	2620	35,000	2 1/4"
18.5	AR111	G53	777915	SR111-18-60D-950-03	12	1/20	W. Flood 60°	5000K	95	1050	1140	35,000	2 1/4"	
PREMIUM	18.5	AR111	G53	777920	SR111-18-09D-827-03	12	1/20	Spot 9°	2700K	80	1190	28680	35,000	2 1/4"
	18.5	AR111	G53	777921	SR111-18-25D-827-03	12	1/20	N. Flood 25°	2700K	80	1190	6420	35,000	2 1/4"
	18.5	AR111	G53	777922	SR111-18-36D-827-03	12	1/20	Flood 36°	2700K	80	1190	2960	35,000	2 1/4"
	18.5	AR111	G53	777923	SR111-18-60D-827-03	12	1/20	W. Flood 60°	2700K	80	1190	1300	35,000	2 1/4"
	18.5	AR111	G53	777924	SR111-18-09D-830-03	12	1/20	Spot 9°	3000K	80	1300	30840	35,000	2 1/4"
	18.5	AR111	G53	777925	SR111-18-25D-830-03	12	1/20	N. Flood 25°	3000K	80	1300	6900	35,000	2 1/4"
	18.5	AR111	G53	777926	SR111-18-36D-830-03	12	1/20	Flood 36°	3000K	80	1300	3200	35,000	2 1/4"
	18.5	AR111	G53	777927	SR111-18-60D-830-03	12	1/20	W. Flood 60°	3000K	80	1300	1400	35,000	2 1/4"

For the most current product information, see www.bulbrite.com/LED

